



WASHING

HIGH SPIN WASHERS HIGH CAPACITY FWH-180C TP2



FEATURES

Touch Plus Control

- 7" touchscreen, user friendly and totally programmable .
- Videos on display, ads, instructions.
- Free software for programming, telemetry, data analysis.
- USB Connection.
- 37 languages.
- 8 dosing signals as standard.

G FACTOR

- High G-Factor 450.

EFFICIENCY

- Energy Optimization.
- Optimal load.
- Low water consumption.

VERSATILITY

- Electric or Hot water.
- WET CLEANING features as standard.

CONNECTIVITY

- IoT - Fagor-Konnect standard.
- Remote technical service.
- Laundry Management system: OPL

ERGONOMICS

- Large Loading Doors: Ø 560 mm.
- Easy opening/closing system for door lock.

MAINTENANCE

- Equivalent parts for all models: contactors, electronic devices, gear.
- Technical menu: traceability, error diagnosis.

OTHERS


- Drum in stainless steel AISI 304.
- 3 water inlets.
- Soft mounted, free standing washers.
- Panels in skin plate.
- Easy to install, no need of fixation to the floor.
- CB and WRAS approved product. .
- High spin washers with suspended drum.

OPTIONS

- Extra dosing pump DB-1.
- Double drain.
- Tropicalized coating.
- Tilting options: frontal or double tilt.
- Automatic weighing sensor system on feet (Not available with tilting kits).
- Relay card with 6 extra dosing signals.
- Stainless steel AISI 304 outer casing.
- Double heating E+S.

DRUM		U.	FWH - 180C TP2	
Load capacity	1:9 / 1:10	Lb.	187.4 / 169.8	
Volume		CU.FT	27.2	
Diameter		In	41.3	
Depth		In	35.1	
GENERAL DETAILS				
Washing speed / Spinning speed		r.p.m.	38 / 875	
G Factor		-	450	
Maximum force transmitted		KN	23 ±4,8	
Frequency-dynamic force		Hz	12.66	
Noise level		dB	< 70	
Coin laundry version		-	No	
Double drain		-	Opt.	
Weighing System / Tilting System		-	Opt.	
SLUICE option		-	No	
DOOR				
Height center door / Height door		In	46.1 / 31.9	
Diameter		In	22.1	
POWER				
Motor		Hp	20.1	
Electric heating power		kW	48/36	
Total electric power (electric model)		kW	51/39	
Total electric power (hw, steam model)		kW	15	
CONNECTIONS		ELECTRIC		STEAM / HOT WATER
Voltage 208-240/60/1~ + G	Nº x AWG / A	-		-
Voltage 230/3~ + G	Nº x AWG / A	4 x 2 / 125A		4 x 6 / 50A
Voltage 440-480/3 ~ + G	Nº x AWG / A	4 x 4 / 90A		4 x 10 / 30A
Steam inlet (Steam model)	inch	3/4"		
Maximum steam consumption (Steam model)	lbs/h	25		
Water inlet	inch	1"		
Water main pressure	Kg/cm2	2-4		
Maximum water consumption	Gal/h	206.2		
Drain	mm/inch	3"		
Drainage capacity	Gal/min	52.8		
DIMENSIONS / PACKING DIMENSIONS				
Net Width / Gross Width		In	55.91 / 63	
Net Depth / Gross Depth		In	64.71 / 71.1	
Net Height / Gross Height		In	74.41 / 76	
Net weight / Gross weight		Lbs.	3969 / 4410	
Volume		Ft3	197.8	

* Programmed No. 2, 100% load



- . Soap dispenser
- . Emergency stop
- . USB port
- . Drain 1
- . Drain 2
- . Electric connection to liquid soap mp
- . Electrical connection
- . Main switch
- 09. Auxiliary water inlet
- 10. Hot water inlet
- 11. Equipotential connection
- 12. Cold water inlet
- 13. Steam output
- 14. Liquid soap connection
- 15. Steam connection
- 16. Air intake
- 17. Ethernet port

		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
FWH-180C	mm	1420	1645	1890	810	560	972	1050	1563	323	1475	1710	1817	508	912	367	595	720	845	1040	1267	160	1353	608	1500	348	830	820
	In	55.91	64.76	74.41	31.89	22.05	38.27	41.34	61.54	12.72	58.07	67.32	71.54	20.00	35.91	14.45	23.43	28.35	33.27	40.94	49.88	6.30	53.27	23.94	59.06	13.70	32.68	32.28